



GAGGIONE SAS Headquarter

3, Rue de la Rolland
01460 Montréal la Cluse
France

☎ +33 4 74 76 12 66

@ contact@gaggione.com

🌐 www.optic-gaggione.com

Sales Team in GAGGIONE

Sandrine Mancuso
France, UK, Italy

@ s.mancuso@gaggione.com

☎ +33 787 87 84 72

Nicolas Golfier
France, Scandinavia, Eastern
and Northern Europe

@ n.golfier@gaggione.com

☎ +33 677 35 50 37

Sonia Andres
France, Spain

@ s.andres@gaggione.com

☎ +33 607 37 20 28

Laurent Barel
Sales & Marketing Director

@ l.barel@gaggione.com

☎ +33 612 04 41 30

PRODUCT MANAGEMENT & BUSINESS DEVELOPMENT

Joni MÄKI

@ j.maki@gaggione.com

☎ +33 638 24 17 51

International Sales Offices

GAGGIONE Americas

Michael Pietro
12833 Surrey Ct.
Palos Park, IL
60464

@ m.pietro@gaggione.com

☎ +1 224 392 0087

GAGGIONE Asia

Zhen Xu
Unit 1808, No. 8, Kuaiji Road,
Jintiandi International building,
Huangpu District,
Shanghai, 200021, China

@ z.xu@gaggione.com

☎ +86 136 5189 6981

GAGGIONE Canada

Stephane Saindon
744 36th Avenue
Montreal, Quebec
H8T3L2

@ s.saindon@gaggione.com

☎ +1 514 928 2179

GAGGIONE DACH

Angelika Aigner
Kreuzstrasse 7
83355 Grabenstätt
Germany

@ a.aigner@gaggione.com

☎ +49 8661 983 44 77

GAGGIONE

SHAPING YOUR LIGHT


NEW



280 x 40 mm
<19 UGR range
POLLUX7X1

POLLUX7X1* GAGGIONE's innovative glare-free family is here. Products are tunable white optimized, without any additional diffusing material. High precision **micro-structured** and **diamond-turned** optics ensures **low surface brightness** and state of the art mixing of colors. Pollux7x1 collimator range comes with antistatic Glossy Black, Matt Black, Glossy White and Matt White louvre options, that makes it easy to develop low glare and discreet luminaire design

Applications



Key Features


Diamond-turned optic, low surface brightness with well controlled, smooth cut-off

Dimensions: (L) 280 mm x (W) 40 mm, (H) 15.8 mm

LED Compatibility: CSP, 2835, 3030, 5050

Typical beam angles: Narrow (15°), Wall Grazer (20°), Medium (30°), Wide (55°), Large (75°), Very Large (83° UGR <19° @1000lm), AS25 (Single Asymmetric shelf), DA35 (Double Asymmetric)

Installation




Louvre versions Antistatic Glossy white (LVRPOLLUX7X101), Antistatic matt white (LVRPOLLUX7X101M)
 Antistatic Glossy black (LVRPOLLUX7X102), Antistatic matt black (LVRPOLLUX7X102M)


PCB compatibility Lumitronix, Tridonic, Osram, MST

Typical beam angles

	FWHM
POLLUX7X1N	~10-15°
POLLUX7X1G	20° (Wall Grazer)
POLLUX7X1M	~35°
POLLUX7X1W	~55°
POLLUX7X1L	~70°
POLLUX7X1VL	~80°
POLLUX7X1E	~20° x ~80°
POLLUX7X1AS25	Asymmetric Shelf
POLLUX7X1DA35	Double Asymmetric



POLLUX7X1AS25
Shelf light version



Competition

AS25 & DA35 application example:



- Light starts 1 meter away from the roof
- Ideal for supermarket shelves
- LED type: 2x Nichia E21

Room dimensions:

Room height: 3.5m

Room width: 2.6m

Distance between luminaires: 2m



POLLUX7X1DA35
Double Asymmetric

Type of Led	POLLUX7X1N	POLLUX7X1G	POLLUX7X1M	POLLUX7X1W	POLLUX7X1L	POLLUX7X1VL	POLLUX7X1E	POLLUX7X1AS25	POLLUX7X1DA35
CSP 3535 HP	✓	✓	✓	✓	✓	✓	✓	✓	✓
2835 x 1 3030 x 1 3535 x 1	✗	✓	✓	✓	✓	✓	✓	✓	✗
2835 X 2 3030 X 2 5050 X 1	✗	✓	✓	✓	✓	✓	✓	✓	✗
CSP X 4 2835 X 4 3030 X 4	✗	✗	✗	✓	✓	✓	✗	✗	✗
Tunable white	✗	✗	✗	✓	✓	✓	✗	✗	✗